



呼径	外径			肉厚			全長			摘要
	OD	t		L						
		素地	研磨	素地	研磨	素地	研磨	素地	研磨	
1S	25.4	+0.25	+0.25	1.2	+0.3	+0.3		+2.0	+2.0	
		-0.25	-0.35		-0.15	-0.3		-2.0	-2.0	
1.5S	38.1	+0.25	+0.25	1.2	+0.3	+0.3		+2.0	+2.0	
		-0.25	-0.35		-0.15	-0.3		-2.0	-2.0	
2S	50.8	+0.25	+0.25	1.5	+0.3	+0.3		+2.0	+2.0	
		-0.25	-0.35		-0.25	-0.35		-2.0	-2.0	
2.5S	63.5	+0.3	+0.3	2	+0.35	+0.35		+2.0	+2.0	
		-0.3	-0.4		-0.3	-0.4		-2.0	-2.0	
3S	76.3	+0.3	+0.3	2	+0.4	+0.4		+2.0	+2.0	
		-0.3	-0.4		-0.3	-0.4		-2.0	-2.0	
4S	101.6	+0.5	+0.5	2	+0.4	+0.4		+2.0	+2.0	
		-0.5	-0.6		-0.4	-0.5		-2.0	-2.0	
10A										
15A	21.7			2.1						

摘要

図番	NGS-HL01	承認	審査	作成	 <b>株式会社ナガセ</b>
品名	片ヘルールパイプ				
材質	SUS304、SUS316L				
作成	15.08.24				