


| 呼径 | 外径 | | | 肉厚 | | | 面間 | | | 摘要 |
|------|-------|----------------|----------------|-----|---------------|---------------|-------|----------------|----------------|----|
| | OD | 素地 | | T | 素地 | | A | 素地 | | |
| | | 研磨 | 研磨 | | 研磨 | 研磨 | | | | |
| 1S | 25.4 | +0.25 -0.25 | +0.25 -0.35 | 1.2 | +0.3 -0.15 | +0.3 -0.25 | 34.0 | +0.5 -0.5 | +0.5 -0.5 | |
| 1.5S | 38.1 | +0.25 -0.25 | +0.25 -0.35 | 1.2 | +0.3 -0.15 | +0.3 -0.25 | 49.0 | +0.5 -0.5 | +0.5 -0.5 | |
| 2S | 50.8 | +0.25 -0.25 | +0.25 -0.35 | 1.5 | +0.3 -0.25 | +0.3 -0.35 | 61.0 | +0.5 -0.5 | +0.5 -0.5 | |
| 2.5S | 63.5 | +0.3 -0.3 | +0.3 -0.4 | 2 | +0.35 -0.3 | +0.35 -0.4 | 84.0 | +0.5 -0.5 | +0.5 -0.5 | |
| 3S | 76.3 | +0.3 -0.3 | +0.3 -0.4 | 2 | +0.4 -0.3 | +0.4 -0.4 | 89.0 | +0.5 -0.5 | +0.5 -0.5 | |
| 4S | 101.6 | +0.5 -0.5 | +0.5 -0.6 | 2 | +0.4 -0.4 | +0.4 -0.5 | 133.4 | +0.75 -0.75 | +0.75 -0.75 | |
| 10A | | | | | | | | | | |
| 15A | 21.7 | | | 2.1 | | | 32.7 | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

摘要

| | | | | | |
|----|----------------|----|----|----|--|
| 図番 | NGS-EL05 | 承認 | 審査 | 作成 |  株式会社ナガセ |
| 品名 | サニタリー溶接式エルボ | | | | |
| 材質 | SUS304、SUS316L | | | | |
| 作成 | 15.08.18 | | | | |